



Printing date 04.10.2022 Version number 1.08 Revision: 04.10.2022

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Metal -protection Zapon laquer satin-finish
- · Article number: 7008698, 7008798, 7008898
- · UFI: VS20-C0UV-C00V-0NKS
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Material for hobby and creative art
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: CREARTEC trend-design-gmbh Lauenbühlstr. 59 D-88161 LINDENBERG DEUTSCHLAND
- Further information obtainable from:

Product safety department info@creartec.info

• 1.4 Émergency telephone number:

During opening hours: +49 8381 80740-0

Mon -Thu from 08.30 to 16.30

and Fri from 08.30 to 12.30

Emergency calls: +49 151 44613864 (24h)

## **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS02

GHS05

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling: butan-1-ol

Version number 1.08 Revision: 04.10.2022 Printing date 04.10.2022

Trade name: Metal -protection Zapon laquer satin-finish

(Contd. of page 1)

ethyl acetate

#### · Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

### Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair). Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Labelling of packages where the contents do not exceed 125 ml

### Hazard pictograms







GHS02

GHS05

# · Hazard-determining components of labelling:

butan-1-ol ethyl acetate

#### · Hazard statements

· Signal word Danger

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · 2.3 Other hazards

### · Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

### · 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5	ethyl acetate  Flam. Liq. 2, H225;  Eye Irrit. 2, H319; STOT SE 3, H336	> 25 – ≤ 50%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9	xylene ♠ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	> 25 – ≤ 50%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1	n-butyl acetate  Flam. Liq. 3, H226;  STOT SE 3, H336	> 10 – < 20%
CAS: 9004-70-0 EC number: 618-392-2	nitrocellulose solutions, with not more than 12.6% nitrogen, by dry mass, and not more than 55% nitrocellulose  § Flam. Sol. 1, H228	> 2.5 – ≤ 10%
		(Contd. on page 3)

Printing date 04.10.2022 Version number 1.08 Revision: 04.10.2022

Trade name: Metal -protection Zapon laquer satin-finish

(Contd. of page 2)

CAS: 71-36-3 | butan-1-ol | ≥ 3 - < 10%

EINECS: 200-751-6 | ♠ Flam | Lig. 3 H226: ♠ Five Dam 1 H318: ♠ Acute Tox 4 H302: Skin

• Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

- EU -

Printing date 04.10.2022 Version number 1.08 Revision: 04.10.2022

Trade name: Metal -protection Zapon laquer satin-finish

(Contd. of page 3)

### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.

### Ingredients with limit values that require monitoring at the workplace:

#### 141-78-6 ethyl acetate

IOELV Short-term value: 1468 mg/m³, 400 ppm

Long-term value: 734 mg/m³, 200 ppm

1330-20-7 xylene

IOELV Short-term value: 442 mg/m³, 100 ppm

Long-term value: 221 mg/m³, 50 ppm

Skin

123-86-4 n-butyl acetate

IOELV Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Colour: Whitish
Odour: Solvent-like
Odour threshold: Not determined.

· **pH-value:** Mixture is non-polar/aprotic.

(Contd. on page 5)

Printing date 04.10.2022 Version number 1.08 Revision: 04.10.2022

Trade name: Metal -protection Zapon laquer satin-finish

(Contd. of page 4)

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: ≥ 77 °C

· Flash point:  $\geq$  -4 °C

Flammability (solid, gas): Highly flammable.
 Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures

are possible.

· Explosion limits:

Lower:
Upper:

Vapour pressure at 20 °C:

Density at 20 °C:

Relative density

Vapour density

Evaporation rate

≥ 1.1 Vol %

≤ 11.5 Vol %

≤ 97 hPa

0.917 g/cm³

Not determined.

Not determined.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic at 20 °C:** 30 s (DIN 53211/4)

· Solvent content:

 Organic solvents:
 86.6 %

 VOC (EC)
 794.3 g/l

 86.6 %

Solids content: 14.0 %

• 9.2 Other information No further relevant information available.

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

Printing date 04.10.2022 Version number 1.08 Revision: 04.10.2022

Trade name: Metal -protection Zapon laquer satin-finish

(Contd. of page 5)

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue		
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	
HP3	Flammable	
HP4	Irritant - skin irritation and eye damage	
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
HP6	Acute Toxicity	

3

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

## **SECTION 14: Transport information**

· 14.1 UN-Number

· ADR, IMDG, IATA UN1263

14.2 UN proper shipping name

· ADR 1263 PAINT
· IMDG, IATA PAINT

· 14.3 Transport hazard class(es)

· ADR, IMDG, IATA



· Class 3 Flammable liquids.

·Label

· 14.4 Packing group · ADR, IMDG, IATA

· **14.5 Environmental hazards:** Not applicable.

• 14.6 Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code):
 EMS Number:
 Stowage Category
 33
 F-E,S-E
 B

· 14.7 Transport in bulk according to Annex II of Marpol

and the IBC Code Not applicable.

(Contd. on page 7)

Printing date 04.10.2022 Version number 1.08 Revision: 04.10.2022

Trade name: Metal -protection Zapon laquer satin-finish

(Contd. of page 6) · Transport/Additional information:

· ADR

· Limited quantities (LQ) Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· Transport category Tunnel restriction code D/E

· Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

UN "Model Regulation": UN 1263 PAINT, 3, II

# **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H228 Flammable solid.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. on page 8)

Printing date 04.10.2022 Version number 1.08 Revision: 04.10.2022

Trade name: Metal -protection Zapon laquer satin-finish

(Contd. of page 7)

· Department issuing SDS: Product safety department

· Contact: Dr. B. Gangnus

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
ELINCS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids — Category 2 Flam. Liq. 3: Flammable liquids — Category 3 Flam. Sol. 1: Flammable solids — Category 1

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Regulation (EC) No. 1272/2008 on the classification, labeling and packaging of substances and mixtures.

Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830 / EU.

Transport of dangerous goods by road, rail or inland waterways (ADR / RID / ADN).

International Code for the Transport of Dangerous Goods by Sea Ships (IMDG).

Dangerous Goods Regulations (DGR) for the air transport (IATA).

EU -