according to 1907/2006/EC, Article 31

Printing date 08.03.2023 Version number 10 (replaces version 9) Revision: 08.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier

Provetro UV + Antispatter - Trade name: AG20-00Q0-R009-84S7 - HFI:

- 1.2 Relevant identified uses of the

substance or mixture and uses advised against

Identified use: intended for professional use only!

- Application of the substance / the mixture Coating - 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: HAVERKAMP GmbH Zum Kaiserbusch 26-28

48165 Münster Tel. 0251 / 62620 Fax: 0261 / 6262181

- Further information obtainable from: research & development

Medical Emergency information in case of poisoning: - 1.4 Emergency telephone number:

Poison Information Center Mainz - 24 h - Phone: +49 (0) 6131 19240

(advisory service in German or English language)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008

H226 Flammable liquid and vapour. Flam. Liq. 3

Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction. Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- 2.2 Label elements

- Labelling according to Regulation (EC) No

1272/2008 - Hazard pictograms The product is classified and labelled according to the GB CLP regulation.







- Signal word Warning

- Hazard-determining components of

labelling:

aliphatic polyisocyanate

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Isophorondiisocvanate homopolymer

Urethane bis Oxazolidine benzotriazole derivatives

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl

sebacate

hexahydromethylphthalic anhydride H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects.

- Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- Additional information: EUH204 Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

- 2.3 Other hazards

- Hazard statements

- Results of PBT and vPvB assessment

- PBT: Not applicable. - vPvB: Not applicable.

according to 1907/2006/EC, Article 31

Printing date 08.03.2023 Version number 10 (replaces version 9) Revision: 08.03.2023

Trade name: Provetro UV + Antispatter

SECTION 3: Composition/information on ingredients

Urethane bis Oxazolidine

(Contd. of page 1)

≥2.5-<10%

≥0.25**-**<0.5%

- 3.2 Mixtures - Description:	Mixture: consisting of the following components.	
- Dangerous components:		
CAS: 426822-87-9 EC number: 642-395-8	aliphatic polyisocyanate Skin Sens. 1, H317	25-50%
CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	10-12.5%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	10-12.5%
CAS: 53880-05-0 EC number: 931-312-3 Reg.nr.: 01-2119488734-24	Isophorondiisocyanate homopolymer Skin Sens. 1B, H317; STOT SE 3, H335	2.5-10%

EINECS: 261-879-6
Reg.nr.: 01-2119983487-19

EC number: 918-668-5
Reg.nr.: 01-2119455851-35
Reg.nr.: 01-2119455851-35
CAS: 25550-51-0
EINECS: 247-094-1
Resp. Sens. 1, H334; Eye Dam. 1, H318; Skin Sens. 1, H317

Aquatic Chronic 2, H411; Eye Irrit. 2, H319; Skin Sens. 1, H317

2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2.5-10%
2

EINECS: 223-861-6 Index number: 615-008-00-5 Sens. 1, H330; Resp. Sens. 1, H334; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %

ELINCS: 400-830-7 Index number: 607-176-00-3 Reg.nr.: 01-0000015075-76 Aquatic Chronic 2, H411; Skin Sens. 1A, H317

CAS: 1065336-91-5 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl ≥0.1-<0.25%

EC number: 915-687-0 sebacate Reg.nr.: 01-2119491304-40 Repr. 2, H361f; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317

CAS: 59719-67-4

CAS: 4098-71-9

- SVHC

- After inhalation:

- After skin contact:

Index number: 607-241-00-6 Reg.nr.: 01-2119845474-33

25550-51-0 hexahydromethylphthalic anhydride

Additional information:
 For the wording of the listed hazard phrases refer to section 16.

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours

after the accident.

Do not leave affected persons unattended. Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment in case of complaints.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Protect unharmed eye.

If symptoms persist consult doctor.

After swallowing:4.2 Most important symptoms and effects,

both acute and delayed

No further relevant information available.

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Printing date 08.03.2023 Version number 10 (replaces version 9) Revision: 08.03.2023

Trade name: Provetro UV + Antispatter

 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

(Contd. of page 2)

SECTION 5: Firefighting measures

- 5.1 Extinguishing media

- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- For safety reasons unsuitable extinguishing

agents:

- 5.2 Special hazards arising from the

substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Nitrogen oxides (NOx) Carbon monoxide (CO)

Water with full jet

- 5.3 Advice for firefighters

- Protective equipment:

Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

Additional information
 Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective

equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation Keep away from ignition sources.

- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Prevent from spreading (e.g. by damming-in or oil barriers). Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment

and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.

Prevent formation of aerosols. Use only in well ventilated areas.

- Information about fire - and explosion

protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and

receptacles:

Store only in the original receptacle.

- Information about storage in one common

storage facility:

otore only in the original receptable

- Further information about storage

conditions:

Store away from foodstuffs.

Store in dry conditions.

Protect from frost.

Recommended storage temperature: 5-30 °C

Keep container tightly sealed.

- 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

according to 1907/2006/EC, Article 31

Version number 10 (replaces version 9) Revision: 08.03.2023 Printing date 08.03.2023

Trade name: Provetro UV + Antispatter

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

Sk

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³

Sen; as -NCO

- Regulatory information

WEL: EH40/2020

- Ingredients with biological limit values:

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

BMGV 1 µmol creatinine/mol

Medium: urine

Sampling time: At the end of the period od exposure

Parameter: isocyanate-derived diamine

- Additional information: The lists valid during the making were used as basis.

- 8.2 Exposure controls

- Appropriate engineering controls No further data; see item 7.

- Individual protection measures, such as personal protective equipment

- General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

When used properly and under normal conditions, breathing protection is not required. - Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

Respiratory protection - Gas filters and combination filters according to (DIN EN 141)

- Hand protection



Protective gloves

Check protective gloves prior to each use for their proper condition.

Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the

preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the

degradation

After use of gloves apply skin-cleaning agents and skin cosmetics.

- Material of gloves Recommended materials:

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.5 mm

Penetration time (min.): < 480

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality

and varies from manufacturer to manufacturer.

- Penetration time of glove material The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions.

Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- As protection from splashes gloves made of

the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.1 mm

Penetration time (min.): < 10

- Eye/face protection



Tightly sealed goggles

Protective goggles and facial protection - Classification according to EN 166

- Body protection: protective clothing (EN 13034)

> GB (Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 08.03.2023 Version number 10 (replaces version 9) Revision: 08.03.2023

Trade name: Provetro UV + Antispatter

(Contd. of page 4)

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Colour: According to product specification - Odour: Characteristic

- Odour threshold: Not determined. - Melting point/freezing point: Undetermined. - Boiling point or initial boiling point and boiling range 155 °C

- Flammability Not applicable.

- Lower and upper explosion limit

- Lower: Not determined. Not determined. - Upper: - Flash point: 48 °C

- Decomposition temperature: Not determined. Not determined. - pH

- Viscosity:

- Kinematic viscosity at 20 °C 2,000 mm²/s - Dynamic: Not determined.

- Solubility

- water: Not miscible or difficult to mix. - Partition coefficient n-octanol/water (log value) Not determined.

- Density and/or relative density - Density at 20 °C: 1.03 g/cm³ - Relative density Not determined.

- 9.2 Other information

- Appearance:

- Vapour density

- Form: Fluid

- Important information on protection of health and environment, and on

safety.

- Auto-ignition temperature: Product is not selfigniting.

- Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are

possible.

Not determined.

- Solvent separation test:

28.60 % - VOC (EC) - Change in condition

- Evaporation rate Not determined.

- Information with regard to physical hazard classes - Explosives Void - Flammable gases Void - Aerosols Void - Oxidising gases Void

- Gases under pressure Void

- Flammable liquids Flammable liquid and vapour.

- Flammable solids Void - Self-reactive substances and mixtures Void - Pyrophoric liquids Void - Pyrophoric solids Void - Self-heating substances and mixtures Void

- Substances and mixtures, which emit flammable gases in contact with

water Void - Oxidising liquids Void - Oxidising solids Void - Organic peroxides Void - Corrosive to metals Void - Desensitised explosives Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability

- Thermal decomposition / conditions to be

avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Printing date 08.03.2023 Version number 10 (replaces version 9) Revision: 08.03.2023

Trade name: Provetro UV + Antispatter

No further relevant information available. - 10.4 Conditions to avoid

- 10.5 Incompatible materials: No further relevant information available. - 10.6 Hazardous decomposition products: No dangerous decomposition products known. (Contd. of page 5)

SECTION 11: Toxicological information

44.4 Information on hazard alassas as defined in Population (EC) No. 1272/2009

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 - Acute toxicity Harmful if inhaled.			
- LD/LC50 values relevant for classification:			
64742-95	64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)	
108-65-6	-	<i>y</i> -1-methylethyl acetate	
Oral	LD50	8,532 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rat)	
Inhalative	LC50/4 h	35.7 mg/l (rat)	
53880-05	-0 Isophor	ondiisocyanate homopolymer	
Oral	LD50	>14,000 mg/kg (rat) (OECD 401)	
59719-67	-4 Urethan	e bis Oxazolidine	
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rab)	
hydrocar	bons, C9,	aromatic	
Oral	LD50	>3,492 mg/kg (rat) (OECD 401)	
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)	
25550-51	-0 hexahyo	dromethylphthalic anhydride	
Oral	LD50	>5,000 mg/kg (rat)	
4098-71-9	3-isocyaı	natomethyl-3,5,5-trimethylcyclohexyl isocyanate	
Inhalative	LC50/4 h	0.05 mg/l (ATE)	
benzotriazole derivatives			
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)	
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)	
	1065336-91-5 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		
Oral	LD50	3,230 mg/kg (rat) (OECD-guidline 423)	
Dermal	LD50	>3,170 mg/kg (rat) (OECD Guideline 402 (Acute Dermal Toxicity))	
- Skin corr	- Skin corrosion/irritation Based on available data, the classification criteria are not met.		

Skin corrosion/irritation Based on available data, the classification criteria are not met. - Serious eye damage/irritation Based on available data, the classification criteria are not met.

- Respiratory or skin sensitisation May cause an allergic skin reaction.

- Germ cell mutagenicity Based on available data, the classification criteria are not met. - Carcinogenicity Based on available data, the classification criteria are not met. - Reproductive toxicity Based on available data, the classification criteria are not met. - STOT-single exposure Based on available data, the classification criteria are not met. - STOT-repeated exposure Based on available data, the classification criteria are not met. - Aspiration hazard Based on available data, the classification criteria are not met.

- 11.2 Information on other hazards

- Endocri	- Endocrine disrupting properties		
128-37-0	2,6-di-tert-butyl-p-cresol	List II	
541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	List II	
556-67-2	octamethylcyclotetrasiloxane	List II, III	
540-97-6	Dodecamethylcyclohexasiloxane	List II	

SECTION 12: Ecological information

- 12.1 Toxicity

12.1 10/10	my		
- Aquatic toxicity:			
64742-95-	64742-95-6 Solvent naphtha (petroleum), light arom.		
LL 50	9.2 mg/l (fish) (96h; OECD 203)		

(Contd. on page 7)

according to 1907/2006/EC, Article 31

Printing date 08.03.2023 Version number 10 (replaces version 9) Revision: 08.03.2023

Trade name: Provetro UV + Antispatter

		(Contd. of page 6)		
EC50	3.2 mg/l (Daphnia magna) (48h;	OECD 202)		
EC50	2.6 mg/l (Pseudokirchneriella su			
108-65-6	2-methoxy-1-methylethyl acetate			
	h >100 mg/l (oryzias latipes (Ricef			
	161 mg/l (fis)			
53880-0	5-0 Isophorondiisocyanate homo	polymer		
		chtlinie 67/548/EWG, Anhang V, C.1.)		
EC50	>3.36 mg/l (Daphnia magna) (Ol	· · · · · · · · · · · · · · · · · · ·		
EC50	>10,000 mg/l (Belebtschlamm) (, and the second		
59719-67	7-4 Urethane bis Oxazolidine	<i>'</i>		
EC50	87.1 mg/l (Daphnia magna) (48h			
EC50	18.6 mg/l (Selenastrum capricon	nutum) (72h)		
hydroca	rbons, C9, aromatic			
LL 50	9.2 mg/l (Oncorhynchus mykiss	(Regenbogenforelle)) (96h; OECD 203)		
EL50	2.9 mg/l (Pseudokirchneriella su	bcapitata) (72h; OECD 201)		
	3.2 mg/l (Daphnia magna) (48h;	OECD 202)		
EC50	>99 mg/l (Belebtschlamm) (10 m	nin.; OECD 209)		
benzotri	azole derivatives			
NOEC	100 mg/kg (Eisenia fetida/foetida	a) (56d; OECD 222)		
LC50/96	h 2.8 mg/l (Oncorhynchus mykiss	(Regenbogenforelle)) (OECD 203; ISO 7346; 84/449/EWG,C1 stat.)		
EC50 >1,000 mg/l (Belebtschlamm) (3h; OECD 209)		h; OECD 209)		
EC50	4 mg/l (Daphnia magna) (48h;)			
EC10	10 mg/l (Pseudokirchneriella sub	capitata) (72h; OECD 201)		
EC50	>100 mg/l (Pseudokirchneriella s	subcapitata) (72h; OECD 201)		
NOEC	0.78 mg/l (Daphnia magna) (21d	; OECD 202, Part 2)		
1065336	-91-5 Reaction mass of bis(1,2,2,	6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		
EC50	0.42 mg/l (ALGAE) (OECD 201)			
LC50	0.9 mg/l /72 h (fish) (OECD 203	(96 hr))		
	sistence and degradability	No further relevant information available.		
	accumulative potential	No further relevant information available.		
	bility in soil sults of PBT and vPvB assessmer	No further relevant information available.		
- 12.5 Kes - PBT:	suits of PBT and VPVB assessmen	Not applicable.		
- vPvB:		Not applicable.		
- 12.6 End	locrine disrupting properties	For information on endocrine disrupting properties see section 11.		
	er adverse effects			
- Remark:		Toxic for fish		
- Addition - General	nal ecological information:	Also poisonous for fish and plankton in water bodies.		
- General	110.603.	Toxic for aquatic organisms		
		Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water		
		Do not allow product to reach ground water, water course or sewage system.		

SECT	ION 13:	Disposa	i consid	lerations

- 13.1 Waste treatment methods

- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal according to official regulations

	- European waste catalogue		
ĺ		5 01* waste isocyanates	
ſ	15 01 10*	packaging containing residues of or contaminated by hazardous substances	
	17 02 03	17 02 03 plastic	

Danger to drinking water if even small quantities leak into the ground.

- Uncleaned packaging:

- **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 8)

Safety data sheet according to 1907/2006/EC, Article 31

Version number 10 (replaces version 9) Printing date 08.03.2023 Revision: 08.03.2023

Trade name: Provetro UV + Antispatter

(Contd. of page 7)

SECTION 14: Transport information	
- 14.1 UN number or ID number - ADR, IMDG, IATA	UN1263
- 14.2 UN proper shipping name - ADR - IMDG - IATA	1263 PAINT, ENVIRONMENTALLY HAZARDOUS PAINT, MARINE POLLUTANT PAINT
- 14.3 Transport hazard class(es)	
- ADR	
- Class - Label	3 (F1) Flammable liquids. 3
- IMDG	
- Class - Label	3 Flammable liquids. 3
- IATA	
- Class - Label	3 Flammable liquids. 3
- 14.4 Packing group - ADR, IMDG, IATA	III
- 14.5 Environmental hazards: - Marine pollutant:	Product contains environmentally hazardous substances: Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate Yes Symbol (fish and tree)
- Special marking (ADR):	Symbol (fish and tree)
 - 14.6 Special precautions for user - Hazard identification number (Kemler code): - EMS Number: - Stowage Category 	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
- 14.7 Maritime transport in bulk according to IMO instrun	nents Not applicable.
- Transport/Additional information: - ADR - Limited quantities (LQ) - Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
- Transport category - Tunnel restriction code	D/E
- IMDG - Limited quantities (LQ) - Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
	(Contd. on page 9)

according to 1907/2006/EC, Article 31

Version number 10 (replaces version 9) Revision: 08.03.2023 Printing date 08.03.2023

Trade name: Provetro UV + Antispatter

- UN "Model Regulation": UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS (Contd. of page 8)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the

application of lower-tier requirements - Qualifying quantity (tonnes) for the

200 t

application of upper-tier requirements

500 t

- REGULATION (EC) No 1907/2006 ANNEX

XVII

Conditions of restriction: 3, 74

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

- Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

- Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- National regulations:
- Substances of very high concern (SVHC) according to UK REACH

25550-51-0 hexahydromethylphthalic anhydride

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The safety data sheet issued is also compliant with the regulation Annex I of Regulation (EU) no. 453/2010 and Annex II of Regulation (EU) no. 2020/878.

- Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

May cause allergy or asthma symptoms or breathing difficulties if inhaled. H334

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects. H411

EUH066 Repeated exposure may cause skin dryness or cracking. EUH204 Contains isocyanates. May produce an allergic reaction.

- Department issuing SDS: research & development - Contact: research & development

- Date of previous version: 07.02.2023

- Version number of previous version:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International - Abbreviations and acronyms:

Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

(Contd. on page 10)

according to 1907/2006/EC, Article 31

Version number 10 (replaces version 9) Printing date 08.03.2023 Revision: 08.03.2023

Trade name: Provetro UV + Antispatter

(Contd. of page 9) ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

PB1: Persistent, Bloaccumulative and roxic VPVB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 1: Acute toxicity – Category 1 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A Skin Sens. 1B: Skin sensitisation – Category 1B Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard — Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 2

- www.echa.europa.eu

- www.baua.de

IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance:

- www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp

- www.dguv.de/ifa/gestis/gestis-dnel-liste

- * Data compared to the previous version altered.

- Sources

GB

(Contd. on page 11)

according to 1907/2006/EC, Article 31

Version number 10 (replaces version 9) Revision: 08.03.2023 Printing date 08.03.2023

See section 1 of the annex to the Safety Data Sheet.

Trade name: Provetro UV + Antispatter

(Contd. of page 10)

Annex: Exposure scenario

- Description of the activities / processes covered in the Exposure Scenario

- Conditions of use

- Duration and frequency

- Physical parameters - Physical state

- Concentration of the substance in the

mixture

- Other operational conditions

- Other operational conditions affecting

environmental exposure

- Other operational conditions affecting

worker exposure

- Other operational conditions affecting

consumer exposure

Other operational conditions affecting consumer exposure during the use of the

product

- Risk management measures

- Worker protection

- Organisational protective measures

- Technical protective measures

- Personal protective measures

No special measures required.

Ensure that suitable extractors are available on processing machines

Do not inhale gases / fumes / aerosols.

Use product only in enclosed systems.

Avoid contact with the skin.

Protective gloves

Not applicable.

5 workdays/week.

The substance is main component.

Avoid long-term or repeated skin contact.

Use only on hard ground.

Avoid contact with the skin.

No special measures required.

Fluid

Check protective gloves prior to each use for their proper condition. Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

After use of gloves apply skin-cleaning agents and skin cosmetics.

When used properly and under normal conditions, breathing protection is not required.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

Respiratory protection - Gas filters and combination filters according to (DIN EN 141)

- Measures for consumer protection

- Environmental protection measures

- Water

- Soil

- Disposal measures

- Disposal procedures

- Exposure estimation - Consumer

- Waste type

Do not allow to reach sewage system.

Prevent contamination of soil.

Ensure adequate labelling.

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Partially emptied and uncleaned packaging

Not relevant for this Exposure Scenario.

GB